



We proudly introduce AJW-114B

The equipment mentioned in this document has either been patented and/or has a patent pending status

Capabilities

- 1- Injection of up to 60 Gallons Per Minute.
- 2- Utilizing Pure De-Ionized water.
- 3- Heated Tanks of up to 160 degree F of water or detergent.
- 4- Multiple Engine Washing
- 5- Effluent Collection Suit
- 6- Effluent Treatment System. (optional)
- 7- Being able to be towed in and around an airport.

GTG On-Wing Engine Compressor Washing System (AJW-114B)

The standard system consists of two tanks. One 60 Gallon tank to hold pure de-ionized water, and one 60 Gallon tank to hold more pure de-ionized water or detergent.

The pure water/detergent tanks can electrically heat up the water/detergent content up to 160 Degrees Fahrenheit through an On- Demand water/detergent heating system.

AJW-114B also utilizes a de-ionization filtration system which allows regular tap water to become 100% pure, Mineral-free de-ionized water before entering the tanks.

The electrically driven pumps on the metal frame of the rig is capable of delivering up to 30 GPM per pump (60 GPM for both pumps) of adjustable pressurized fluid into the delivery hoses. Unlike other injection systems, our system eliminates the hassle of carrying and servicing nitrogen bottles to pressurize the tanks.

The delivery hoses could be (depending on the operator's choice) connected to J shaped probes or J hooks (2 provided with basic system) which are entered from the back of the bypass duct and then held tight against the core case in front of the 1st stage stators ahead of the 2nd stage compressors. This is to ensure 100% water/detergent injection into the engine core. This method also eliminates opening of the Cowlings and Thrust Reversers and reduces the time spent for a complete engine wash.

AJW-114B has a sturdy tow bar and hitch which could easily be transported in and around an airport at speeds of up to 15-20 MPH.

The overall dimensions: 8 feet long (including the tow bar), 4 feet tall and 4 feet wide.

The control panel on the rig has illuminated gauges which allows the operator to read the fluid quantity and temperature in both tanks and turn switches to activate the pumps for water/fluid delivery.

On Board Equipment

- ✓ Water/Detergent Injection Delivery System (Standard)
- ✓ Effluent Collection Suit (Capturing System) (Standard)
- ✓ Waste Water/Detergent Treatment System (Optional)
- ✓ De-ionizing System (Standard)
- ✓ 2 Injection Probes (J Hooks) with different lengths extensions (Standard)



Our collection suit system is the only system in the world that collects ALL the effluent coming out of the tail pipe and the engine while performing engine compressor wash. This system encapsulates the engine. There is a screened vent on top of the suit to allow excess air to escape the suit to prevent over inflation of the suit. The material this suit is made of is of a space age fabric which is extremely light and durable and has proved to be ideal for its purpose. This suit conveniently fits in a duffle bag.

The material and the workmanship of this suit is rugged enough so it could be used over and over again for years to come if handled per manufacturer's specs.

This package also comes with a repair kit in case any part of the fabric is torn while being used or handled and a manual for ease of operation.

